



Measurements International
Metrology is Our Science, Accuracy is Our Business™

PROGRAMMABLE DC VOLTAGE SOURCE

MODEL 1000B

- 0 to 100 V
- Stability < 1 ppm for 8 Hours
- Absolute Accuracy < 40 ppm
- Noise < 10 μ V



MODEL 1000B PROGRAMMABLE DC VOLTAGE SOURCE

The model 1000B was developed as a low drift, stable, low noise 110 Volt Programmable DC Source for use with the model 6000B High Resistance Bridge. The 1000B output is protected against accidental shorting and will not energize if voltage is detected on the output terminals. Revised software is included for the 6000B to fully automate the voltage test points and also includes a calibration routine designed specifically for the 1000B using only an 8.5 digit DMM.

Specifications: Rev 1

Range	Resolution	Noise	8 Hour Stability	Accuracy
0-200 mV	0.1 μ V	1.3 μ V	< 5 ppm	40 ppm
0.2-2 V	1 μ V	4 μ V	< 2 ppm	40 ppm
2-20 V	10 μ V	20 μ V	< 1 ppm	40 ppm
20-110 V	100 μ V	100 μ V	< 1 ppm	40 ppm
Performance specifications relative to setpoint				
Warm Up Time		20 Minutes		
Operating Power		110, 120, 220, 240 V – 50/60 Hz		
Operating Environment		18 to 30 °C, 10 to 80 % RH		
Dimensions		133 × 450 × 305 mm		
Product Weight		12 kg		
Shipping Weight		15 kg		
Warranty		3 Years (Parts & Labour)		

Corporate Headquarters

Measurements International
PO Box 2359, 118 Commerce Drive
Prescott, Ontario, Canada K0E 1T0

Phone: 613-925-5934

Fax: 613-925-1195

Email: sales@mintl.com

Toll Free: 1-800-324-4988

Worldwide Offices

MI-USA

Phone: 407-706-0328

Email: sales@mintl.com

MI-China

Phone: +(86) 10-64459890

Email: sales@mintl.com

MI-Europe

Phone: +(420) 731-440-663

Email: sales@mintl.com

MI-Japan

Phone: +(81) 72 39 64 660

Email: kaz@mijpn.com

MI-India

Phone: +(91) 98 10 134 932

Email: sales@MILLP.co.in



www.mintl.com