



Elektro-Automatik



## DATASHEET

# EA-PS 10000 2U

Programmable  
DC Power Supply

# EA-PS 10000 2U 1.5 KW / 3 KW

Programmable DC power supply



## Features

- Wide range input: 110 V - 240 V,  $\pm 10\%$ , 1ph AC
- Active Power-Factor-Correction, typical 0.99
- Very high efficiency of up to 95%
- Voltages from 0 - 60 V up to 0 - 1500 V
- Currents from 0 - 6 A up to 0 - 120 A
- Flexible power regulated DC output stages (autoranging)
- Regulation mode CV, CC, CP, CR with fast crossover
- Digital regulation, high resolution with 16bit ADCs and DACs, selection of voltage regulation speed: Normal, Fast, Slow
- Color 5" TFT display with touch control and intuitive user interface
- Galvanically isolated Share bus for parallel operation of all power classes in the 10000 series
- Master-slave bus for parallel operation of up to 64 units of all power classes in the 10000 series
- Command languages and drivers: SCPI and ModBus, LabVIEW, IVI

## Build-in Interfaces

- USB
- Ethernet
- Analog
- USB Host
- Master-Slave-Bus
- Share-Bus

## Optional Interfaces

- CAN
- CANopen
- RS232
- Profibus
- EtherCAT
- Profinet, with one or two ports
- Modbus, with one or two ports
- Ethernet, with one or two ports

## Software

- EA-Power Control

## Technical data

| General specifications          |                                                                                                                                            |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AC input</b>                 |                                                                                                                                            |
| Voltage, Phases                 | Range 1: 110 - 127 V, $\pm 10\%$ , 1ph AC (with DC output power derating to 1.2 kW or 1.5 kW)<br>Range 2: 208 - 240 V, $\pm 10\%$ , 1ph AC |
| Frequency                       | 45 - 65 Hz                                                                                                                                 |
| Power factor                    | ca. 0.99                                                                                                                                   |
| Leakage current                 | <3.5 mA                                                                                                                                    |
| Inrush current                  | @230 V: ca. 23 A                                                                                                                           |
| Overvoltage category            | 2                                                                                                                                          |
| <b>DC output static</b>         |                                                                                                                                            |
| Load regulation CV              | $\leq 0.05\%$ FS (0 - 100% load, constant output voltage and constant temperature)                                                         |
| Line regulation CV              | $\leq 0.01\%$ FS (110 V - 240 V AC $\pm 10\%$ , constant load and constant temperature)                                                    |
| Stability CV                    | $\leq 0.02\%$ FS (during 8 h of operation, after 30 minutes warm-up, at constant output voltage, load and temperature)                     |
| Temperature coefficient CV      | $\leq 30\text{ppm}/^\circ\text{C}$ (after 30 minutes of warm-up)                                                                           |
| Compensation (remote sense)     | $\leq 5\%$ $U_{\text{Nominal}}$                                                                                                            |
| Load regulation CC              | $\leq 0.1\%$ FS (0 - 100% load, constant output voltage and constant temperature)                                                          |
| Line regulation CC              | $\leq 0.01\%$ FS (110 V - 240 V AC $\pm 10\%$ , constant load and constant temperature)                                                    |
| Stability CC                    | $\leq 0.02\%$ FS (during 8 h of operation, after 30 minutes warm-up, at constant output voltage, load and temperature)                     |
| Temperature coefficient CC      | $\leq 50\text{ppm}/^\circ\text{C}$ (after 30 minutes of warm-up)                                                                           |
| Load regulation CP              | $\leq 0.3\%$ FS (0 - 100% load, constant output voltage and constant temperature)                                                          |
| Load regulation CR              | $\leq 0.3\%$ FS + 0.1% FS current (0 - 100% load, constant output voltage and constant temperature)                                        |
| <b>Protective functions</b>     |                                                                                                                                            |
| OVP                             | Overvoltage protection, adjustable 0 - 110% $U_{\text{Nominal}}$                                                                           |
| OCP                             | Overcurrent protection, adjustable 0 - 110% $I_{\text{Nominal}}$                                                                           |
| OPP                             | Overpower protection, adjustable 0 - 110% $P_{\text{Nominal}}$                                                                             |
| OT                              | Overtemperature protection (DC output shuts down in case of insufficient cooling)                                                          |
| <b>DC output dynamic</b>        |                                                                                                                                            |
| Rise time 10 - 90% CV           | $\leq 20$ ms                                                                                                                               |
| Fall time 90 - 10% CV           | $\leq 20$ ms                                                                                                                               |
| Rise time 10 - 90% CC           | $\leq 10$ ms                                                                                                                               |
| Fall time 90 - 10% CC           | $\leq 10$ ms                                                                                                                               |
| <b>Display accuracy</b>         |                                                                                                                                            |
| Voltage                         | $\leq 0.05\%$ FS                                                                                                                           |
| Current                         | $\leq 0.1\%$ FS                                                                                                                            |
| <b>Insulation</b>               |                                                                                                                                            |
| AC input to DC output           | 3750 Vrms (1 minute, creepage distance >8 mm) *1                                                                                           |
| AC input to case (PE)           | 2500 Vrms                                                                                                                                  |
| DC output to case (PE)          | Depending on the model, see model tables                                                                                                   |
| DC output to interfaces         | 1000 V DC (models up to 360 V rating), 1500 V DC (models from 500 V rating)                                                                |
| <b>Interfaces digital</b>       |                                                                                                                                            |
| Built-in, galvanically isolated | USB, Ethernet (100 MBit) for communication, 1x USB host for data acquisition                                                               |
| Optional, galvanically isolated | CAN, CANopen, RS232, ModBus TCP, Profinet, Profibus, EtherCAT, Ethernet                                                                    |
| <b>Interfaces analog</b>        |                                                                                                                                            |
| Built-in, galvanically isolated | 15 pole D-Sub                                                                                                                              |
| Signal range                    | 0 - 10 V or 0 - 5 V (switchable)                                                                                                           |
| Inputs                          | U, I, P, R, remote control on/off, DC output on/off, resistance mode on/off                                                                |
| Outputs                         | Monitor U and I, alarms, reference voltage, DC output status, CV/CC regulation mode                                                        |
| Accuracy U / I / P / R          | 0 - 10 V: $\leq 0.2\%$ , 0 - 5 V: $\leq 0.4\%$                                                                                             |

\*1 Models up to 80 V DC rating have reinforced insulation while all other models from 200 V DC rating have basic insulation

| General specifications          |                                                                                                                                                                                                                                    |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Device configuration</b>     |                                                                                                                                                                                                                                    |
| Parallel operation              | Up to 64 units of any power class in series 10000, with master-slave bus and Share bus                                                                                                                                             |
| <b>Safety and EMC</b>           |                                                                                                                                                                                                                                    |
| Safety                          | EN 61010-1<br>IEC 61010-1<br>UL 61010-1<br>CSA C22.2 No 61010-1<br>BS EN 61010-1                                                                                                                                                   |
| EMC                             | EN 55011, class B<br>CISPR 11, class B<br>FCC 47 CFR Part 15B, Unintentional Radiator, class B<br>EN 61326-1 include tests according to:<br>- EN 61000-4-2<br>- EN 61000-4-3<br>- EN 61000-4-4<br>- EN 61000-4-5<br>- EN 61000-4-6 |
| Safety protection class         | 1                                                                                                                                                                                                                                  |
| Ingress Protection              | IP20                                                                                                                                                                                                                               |
| <b>Environmental conditions</b> |                                                                                                                                                                                                                                    |
| Operating temperature           | 0 - 50 °C (32 - 122 °F)                                                                                                                                                                                                            |
| Storage temperature             | -20 - 70 °C (-4 - 158 °F)                                                                                                                                                                                                          |
| Humidity                        | ≤80% relative humidity, non-condensing                                                                                                                                                                                             |
| Altitude                        | ≤2000 m (≤6,600 ft)                                                                                                                                                                                                                |
| Pollution degree                | 2                                                                                                                                                                                                                                  |
| <b>Mechanical construction</b>  |                                                                                                                                                                                                                                    |
| Cooling                         | Forced air flow from front to rear, temperature controlled fans                                                                                                                                                                    |
| Dimensions (W x H x D)          | Enclosure: 19" x 2U x 462 mm (18.2 in)<br>Total: 19" x 2U x min. 559 mm (22 in)                                                                                                                                                    |
| Weight                          | 1500 W unit: 9.5 kg (21 lb)                      3000 W unit: 12.7 kg (28 lb)                                                                                                                                                      |

| Technical specifications | PS 10060-60             | PS 10080-60             | PS 10200-25             | PS 10360-15             | PS 10500-10             |
|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| <b>DC output</b>         |                         |                         |                         |                         |                         |
| Voltage range            | 0 - 60 V                | 0 - 80 V                | 0 - 200 V               | 0 - 360 V               | 0 - 500 V               |
| Ripple in CV (rms)       | 10 mV (BW 300 kHz)      | 10 mV (BW 300 kHz)      | 30 mV (BW 300 kHz)      | 30 mV (BW 300 kHz)      | 40 mV (BW 300 kHz)      |
| Ripple in CV (pp)        | 100 mV (BW 20 MHz)      | 100 mV (BW 20 MHz)      | 300 mV (BW 20 MHz)      | 300 mV (BW 20 MHz)      | 500 mV (BW 20 MHz)      |
| Current range            | 0 - 60 A                | 0 - 60 A                | 0 - 25 A                | 0 - 15 A                | 0 - 10 A                |
| Power range *1           | 0 - 1500 W (0 - 1200 W) | 0 - 1500 W (0 - 1200 W) | 0 - 1500 W (0 - 1200 W) | 0 - 1500 W (0 - 1200 W) | 0 - 1500 W (0 - 1200 W) |
| Resistance range         | 0.04 Ω - 80 Ω           | 0.04 Ω - 80 Ω           | 0.25 Ω - 500 Ω          | 0.8 Ω - 1600 Ω          | 2 Ω - 3000 Ω            |
| Output capacity          | 8640 µF                 | 8640 µF                 | 800 µF                  | 330 µF                  | 120 µF                  |
| Efficiency               | ≤94% *2                 | ≤94% *2                 | ≤94.5% *2               | ≤94.5% *2               | ≤95% *2                 |
| <b>Insulation</b>        |                         |                         |                         |                         |                         |
| Negative DC pole <-> PE  | ±600 V DC               | ±600 V DC               | ±1000 V DC              | ±1000 V DC              | ±1000 V DC              |
| Positive DC pole <-> PE  | +600 V DC               | +600 V DC               | +1000 V DC              | +1000 V DC              | +1500 V DC              |
| <b>Article number</b>    | 06230940                | 06230941                | 06230942                | 06230943                | 06230944                |

\*1 The value in brackets applies to the state of derating (power reduction) for 110 to 127 V ±10% utility

\*2 At 100% power and 100% output voltage

| Technical specifications | PS 10750-06             |  |  |  |  |
|--------------------------|-------------------------|--|--|--|--|
| <b>DC output</b>         |                         |  |  |  |  |
| Voltage range            | 0 - 750 V               |  |  |  |  |
| Ripple in CV (rms)       | 50 mV (BW 300 kHz)      |  |  |  |  |
| Ripple in CV (pp)        | 500 mV (BW 20 MHz)      |  |  |  |  |
| Current range            | 0 - 6 A                 |  |  |  |  |
| Power range *1           | 0 - 1500 W (0 - 1200 W) |  |  |  |  |
| Resistance range         | 4 Ω - 6000 Ω            |  |  |  |  |
| Output capacity          | 40 µF                   |  |  |  |  |
| Efficiency               | ≤95% *2                 |  |  |  |  |
| <b>Insulation</b>        |                         |  |  |  |  |
| Negative DC pole <-> PE  | ±1000 V DC              |  |  |  |  |
| Positive DC pole <-> PE  | +1500 V DC              |  |  |  |  |
| <b>Article number</b>    | 06230945                |  |  |  |  |

\*1 The value in brackets applies to the state of derating (power reduction) for 110 to 127 V ±10% utility

\*2 At 100% power and 100% output voltage

| Technical specifications | PS 10060-120            | PS 10080-120            | PS 10200-50             | PS 10360-30             | PS 10500-20             |
|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| <b>DC output</b>         |                         |                         |                         |                         |                         |
| Voltage range            | 0 - 60 V                | 0 - 80 V                | 0 - 200 V               | 0 - 360 V               | 0 - 500 V               |
| Ripple in CV (rms)       | 10 mV (BW 300 kHz)      | 10 mV (BW 300 kHz)      | 30 mV (BW 300 kHz)      | 30 mV (BW 300 kHz)      | 40 mV (BW 300 kHz)      |
| Ripple in CV (pp)        | 100 mV (BW 20 MHz)      | 100 mV (BW 20 MHz)      | 300 mV (BW 20 MHz)      | 300 mV (BW 20 MHz)      | 500 mV (BW 20 MHz)      |
| Current range            | 0 - 120 A               | 0 - 120 A               | 0 - 50 A                | 0 - 30 A                | 0 - 20 A                |
| Power range *1           | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) |
| Resistance range         | 0.02 Ω - 24 Ω           | 0.02 Ω - 40 Ω           | 0.1 Ω - 250 Ω           | 0.4 Ω - 800 Ω           | 1 Ω - 1500 Ω            |
| Output capacity          | 17280 µF                | 17280 µF                | 1600 µF                 | 660 µF                  | 240 µF                  |
| Efficiency               | ≤94% *2                 | ≤94% *2                 | ≤94.5% *2               | ≤94.5% *2               | ≤95% *2                 |
| <b>Insulation</b>        |                         |                         |                         |                         |                         |
| Negative DC pole <-> PE  | ±600 V DC               | ±600 V DC               | ±1000 V DC              | ±1000 V DC              | ±1000 V DC              |
| Positive DC pole <-> PE  | +600 V DC               | +600 V DC               | +1000 V DC              | +1000 V DC              | +1500 V DC              |
| <b>Article number</b>    | 06230946                | 06230947                | 06230948                | 06230949                | 06230950                |

\*1 The value in brackets applies to the state of derating (power reduction) for 110 to 127 V ±10% utility

\*2 At 100% power and 100% output voltage

| Technical specifications | PS 10750-12             | PS 11000-10             | PS 11500-06             |  |  |
|--------------------------|-------------------------|-------------------------|-------------------------|--|--|
| <b>DC output</b>         |                         |                         |                         |  |  |
| Voltage range            | 0 - 750 V               | 0 - 1000 V              | 0 - 1500 V              |  |  |
| Ripple in CV (rms)       | 50 mV (BW 300 kHz)      | 100 mV (BW 300 kHz)     | 150 mV (BW 300 kHz)     |  |  |
| Ripple in CV (pp)        | 500 mV (BW 20 MHz)      | 2000 mV (BW 20 MHz)     | 6500 mV (BW 20 MHz)     |  |  |
| Current range            | 0 - 12 A                | 0 - 10 A                | 0 - 6 A                 |  |  |
| Power range *1           | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) | 0 - 3000 W (0 - 1500 W) |  |  |
| Resistance range         | 2 Ω - 3000 Ω            | 3 Ω - 6000 Ω            | 8 Ω - 6000 Ω            |  |  |
| Output capacity          | 80 µF                   | 60 µF                   | 20 µF                   |  |  |
| Efficiency               | ≤95% *2                 | ≤95% *2                 | ≤95% *2                 |  |  |
| <b>Insulation</b>        |                         |                         |                         |  |  |
| Negative DC pole <-> PE  | ±1000 V DC              | ±1000 V DC              | ±1000 V DC              |  |  |
| Positive DC pole <-> PE  | +1500 V DC              | +1500 V DC              | +1500 V DC              |  |  |
| <b>Article number</b>    | 06230951                | 06230952                | 06230953                |  |  |

\*1 The value in brackets applies to the state of derating (power reduction) for 110 to 127 V ±10% utility

\*2 At 100% power and 100% output voltage

## General

The DC laboratory power supplies in the PS 10000 series from EA Elektro-Automatik convert the energy from the grid into a regulated DC voltage with an efficiency of up to 96%. The PS 10000 series includes single and three phase units, which, together with the wide input range, allows use with practically all global mains voltages. The DC voltage and current are directed by the application and the spectrum ranges from 0 - 60 V to 0 - 2000 V and from 0 - 6 A up to 0 - 1000 A in a single device. The DC supply operates as a flexible output stage with a constant power characteristic (autoranging), and a wide voltage, current and power range. To achieve higher power and current all units are equipped with a master-slave bus. This enables up to 64 parallel connected devices to be combined into one system which can provide up to 1920 kW and 64000 A. Such a system works as a single unit and can use different power classes, only the voltage class must remain constant. In this way a user can construct a 75 kW system from two 30 kW 4U and one 15 kW 3U device from the PS 10000 range. Furthermore, typical laboratory functionality is provided. This includes an extensive function generator, alarm and warning management, various industrial interfaces, software solutions and many more functions.

## AC connection


The DC power supplies in the PS 10000 series are equipped with an active PFC which provides a high efficiency at a low energy consumption. Furthermore, the devices in this series provide a wide input voltage range. It reaches from 110/120 V up to 240 V with 1-phase models and from 208 V to 380/400/480 V with 3-phase models. Hence the devices can be operated in the majority of global grids. They adjust automatically, without additional configuration, to the available grid voltage. In a 110/120 V and 208 V AC grid a derating of the DC output power is automatically set.

## DC output

The DC output of the power supplies in series PS 10000 2U is rated for DC voltages of 0 - 60 V up to 0 - 1500 V, allowing currents of 0 - 6 A up to 0 - 120 A. The flexible output stages (autoranging) provide the user with a wide voltage, current and power range and hence a wider field of working than traditional power supplies.

## DC connection

Connection of the DC output is done via copper blades on the back side of the device. If a system with higher performance is required, the devices are simply connected in parallel. With minimal effort devices can be linked with the vertical copper rails. A cover for contact protection is provided.



## The principle of autoranging

„Autoranging“ is a term used when a programmable DC power supply automatically offers a wider output range of both, voltage and current, to maintain full power across a wide operation range. This type of solution allows the use of a single unit to address multiple voltage and current combinations.

## Interfaces

As standard, 10000s series devices are fitted with the most important interfaces and ports which are all galvanically isolated from the DC input. There is an analog interface which can be parameterized for input and output, control and monitoring, of 0 - 5 V or 0 - 10 V for voltage, current, power and resistance, assorted inputs and outputs as well as USB and Ethernet ports. Further optional industrial interface for plug & play slot complete the portfolio:

- CAN
- CANopen
- RS232
- Profibus
- EtherCAT
- Profinet, with one or two ports
- Modbus, with one or two ports
- Ethernet, with one or two ports

## High performance systems

High power applications can be covered with high power systems of up to 192 kW. These are achieved by using the outputs of many PS 10000 2U devices and connecting them in parallel using copper rails. A 19" cabinet with a height of 42U can hold up to 16 units of 2U and thus form a system of up to 48 kW occupying only 0.6 m<sup>2</sup> (6.5 sqft) of floor space. The master/slave bus allows for up to 6 cabinets with a maximum of 64 units and up to 3 kW each to behave as one unit.

## Master-slave bus and Share bus

When the integrated master-slave bus and Share bus are used, a multi device system behaves as a single device. The buses are simply connected between each device. With the master-slave bus the system data, such as total power and total current, are collected and displayed on the master unit. Warnings and alarms of the slave devices are also clearly displayed. The Share bus cares for a balanced load distribution between the individual units.



## Example representation

In this illustration you can see a fully assembled and wired 240 kW system, realized with 30 kW 4U units.

## Applications


### Relay test in the production

Relay manufacturers must carry out assorted tests on their products during production. For these the coils and contacts are provided with exactly defined voltage and current. For the coil tests, important parameters such as operating, holding and decay current, together with the associated voltages must be checked and documented. For the contacts, not only are the current carrying capability and contact resistance important parameters, but also voltage consistency and disconnect threshold indicate much about the product quality. Testing all these is best supported by an automatic test system. A part of such a system can be the devices of the PS 10000 series with their exact, dynamic, controls of voltage, current, power, and resistance, providing optimal values for the best test results. With their diverse interface connections, they can be integrated into any test system and deliver the necessary data without the need for additional measuring equipment.


### On-board charger test

In an on-board charger test (OBC) the electrical features of the charger must be tested under various conditions. This requires a flexible test system which also provides test data. With the sequencing and logging functions of the software EA-Power Control it allows data to be exported and saved. In this way applications can instantly generate reproducible test results based on dynamic and highly accurate set point and measurement data. To avoid competition between two separate control loops of the device under test (DUT) and the testing device, the voltage regulation speed of the power supply is adjustable. The modes Normal, Fast and Slow allow the PS 10000 devices to be adapted the control characteristics of the on-board charger. Due to the fact that a power supply can only operate as a source, the combination with a sink, here an electronic DC load of ELR 10000 series, might be required.

Technical drawings PS 10000 2U




## Front panel description PS 10000 2U



1. Power switch
2. TFT control Interface, interactive operation and display
3. Rotary knob with push-button for settings and control
4. USB host, uses USB sticks for data logging and sequencing
5. Rotary knob with push-button for settings and control
6. On / off push-button with LED status display

## Rear panel description PS 10000 2U



1. Slot for interfaces
2. Master-slave bus connectors to set up a system for parallel connection
3. Share bus connectors to set up a system for parallel connection
4. Remote sense connectors
5. DC output terminal (copper blades)
6. AC input connector
7. Ethernet interface
8. USB interface
9. Connector (DB15 female) for isolated analog programming, monitor and other functions
10. Grounding connection screw (PE)

**EA Elektro-Automatik GmbH**

Helmholtzstr. 31-37  
41747 Viersen

Phone +49 2162 3785 - 0  
Fax +49 2162 16230  
ea1974@elektroautomatik.com

**[www.elektroautomatik.com](http://www.elektroautomatik.com)**

**EA Elektro-Automatik Inc.**

7926 Convoy Court  
CA, 92111, San Diego

Phone +1 (858) 836 1300  
sales@elektroautomatik.com

**[www.eapowered.com](http://www.eapowered.com)**

