

Passive 1x/10x Voltage Probe

P2220 P2221 Datasheet



Tektronix passive probe solutions provide high reliability and testing accuracy for basic oscilloscope measurements. The P2220 and P2221 are compact passive probes with selectable 1X/10X attenuation designed for use with selected Tektronix oscilloscopes.

Key features

- 1x/10x attenuation
- 200 MHz bandwidth
- 1.5 m length
- UL3111-1, CSA1010.1, EN61010-1, EN61010-2-031, and IEC61010-2-031

Applications

- Relative low-frequency measurements
- Low-frequency computer and telecom measurements
- Power supplies
- Low-frequency amplifiers

P2220 P2221 passive voltage probes

The P2220 and P2221, 200 MHz passive voltage probes permit selection of 1x or 10x attenuation, using a switch located on the probe head.

The P2220 probe is compatible with TDS200, TDS1000, TDS1000B, TDS2000, TDS2000B, and TPS2000 Series oscilloscopes. The P2220 probe also provides floating measurement capability up to 30 V_{RMS} with TPS2000 Series oscilloscopes only. (Note: Do not float with TDS2000, TDS2000B, TDS1000, TDS1000B, or TDS200 Series oscilloscopes.)

The P2221 is compatible with MSO2000 and DPO2000 Series oscilloscopes.

Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

	10X	1x
Bandwidth	DC to 200 MHz	DC to 6 MHz
Probe length	1.5 m	1.5 m
Attenuation ratio	10:1	1:1
Compensation range		All oscilloscopes with 1 M Ω input
	P2220	15 to 25 pF
	P2221	10 to 25 pF
Input capacitance	17.0 pF	110 pF
Input resistance	10 M Ω	1 M Ω
Maximum input voltage	300 V Cat II	150 V Cat II
Maximum voltage between reference lead and earth ground	30 V _{RMS} ¹	30 V _{RMS} ¹


¹ The float voltage must be subtracted from the tip to earth ground voltage. For example, if the reference lead is floated to 30 V_{RMS} while the probe is in the 10x position, the tip voltage to the reference lead is limited to 270 V_{RMS}.

Ordering Information

P2220	Passive Probe, 1x/10x, 200 MHz Passive Voltage Probe Includes retractable hook tip (013-0107-xx), 6-inch ground lead (196-3466-xx), adjustment tool (003-1433-xx), marker band set (016-1315-xx), instruction manual (071-1464-xx). ²
P2221	Passive Probe, 1x/10x, 200 MHz Passive Voltage Probe for MSO/DPO2000 Series oscilloscopes Includes retractable hook tip (013-0107-xx), 6-inch ground lead (196-3466-xx), adjustment tool (003-1433-xx), marker band set (016-1315-xx), instruction manual (071-2335-xx). ²



Tektronix is ISO 14001:2015 and ISO 9001:2015 certified by DEKRA.



CALPLUS
Die Kompetenz in der Messtechnik

CalPlus GmbH
Zentrale Berlin
Heerstraße 32 • 14052 Berlin
Tel.: 030 214982-0 • Fax: 030 214982-50
office@calplus.de • www.calplus.de

CalPlus GmbH
Niederlassung ScopeShop
Normannenweg 30 • 20537 Hamburg
Tel.: 040 3039595-0 • Fax: 040 3039595-50
scopeshop@calplus.de • www.calplus.de

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

25 Jan 2023 51W-17984-4
www.tek.com

Tektronix®