

7703 32-channel, High Speed, Differential Multiplexer Module


Datasheet



The 7703 plug-in module offers 32 channels of 2-pole or 16 channels of 4-pole multiplexer switching that can be configured as two independent banks of multiplexers. The non-latching reed relays provide high speeds and are designed for 300 volt, 500 mA; 10 VA. The relay closures are stored in onboard memory. The 7703 is ideal for RTD and thermistor temperature applications.

Key Features

- 32 channels for general purpose measurements
- Relay actuation time of less than 1ms for high-speed scanning
- Two- or four-wire measurement
- Two 50-pin female D-sub connectors are standard for secure hook-up and quick teardown



Specifications

Capabilities	
Channels 1–32	Multiplex one of 32 2-pole or one of 16 4-pole signals into DMM.
Inputs	
Maximum Signal Level	
Channels (1–32)	300 V DC or rms, 0.5 A switched, 10 W maximum.
Contact Life (typ.)	>5×10 ⁴ operations at max. signal level. >10 ⁸ operations cold switching.
Contact Resistance	<1 Ω at end of contact life.
Contact Potential	<±3 μV typical per contact, 6 μV max. <±3 μV typical per contact pair, 6 μV max.
Offset Current	<100 pA.
Connector Type	50 pin D-sub ×2.
Relay Drive Current	20 mA per channel.
Isolation Between Any Two Terminals	
>10 ⁹ Ω, <200 pF.	
Isolation Between Any Terminal and Earth	
>10 ⁹ Ω, <400 pF.	
Cross Talk (1 MHz, 50 Ω Load)	
<–40 dB.	
Insertion Loss (50 Ω Source, 50 Ω Load)	
<0.35 dB below 1 MHz. <3 dB below 2 MHz.	
Common Mode Voltage	
300 V between any terminal and chassis.	

General

32 Channels	32 channels of 2-pole relay input. All channels configurable to 4-pole.
Relay Type	Reed.
Actuation Time	<1 ms.
Environmental and Safety	
Operating Environment: Specified for 0° to 50°C. Specified to 40% R.H. at 35°C.	
Storage Environment: –25° to 65°C.	
EMC: Conforms to European Union EMC Directive.	
Safety: Conforms to European Union Low Voltage Directive	
RoHS: Conforms to European Union RoHS Directive	
Weight	0.8 kg (1.75 lbs).

Supplied Accessories

7703-306A	50-pin D-Sub Male Shell Connector Kit, quantity 2
-----------	---

Available Accessories

7705-MTC-2	50 Pin Male to Female D-sub Cable, 2 m (6.6 ft).
7788	50-pin D-Sub male connector kit, quantity 2
7790	50-pin male, 50-pin female, 25-pin male D-shell IDC connectors

Available Services

7703-3Y-EW	1-year factory warranty extended to 3 years from date of shipment
------------	---

Ordering Information

7703	32-channel, High Speed, Differential Multiplexer Module
Warranty	1 year

Contact Information:

Australia* 1 800 709 465
Austria 00800 2255 4835
Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Belgium* 00800 2255 4835
Brazil +55 (11) 3759 7627
Canada 1 800 833 9200
Central East Europe / Baltics +41 52 675 3777
Central Europe / Greece +41 52 675 3777
Denmark +45 80 88 1401
Finland +41 52 675 3777
France* 00800 2255 4835
Germany* 00800 2255 4835
Hong Kong 400 820 5835
India 000 800 650 1835
Indonesia 007 803 601 5249
Italy 00800 2255 4835
Japan 81 (3) 6714 3010
Luxembourg +41 52 675 3777
Malaysia 1 800 22 55835
Mexico, Central/South America and Caribbean 52 (55) 56 04 50 90
Middle East, Asia, and North Africa +41 52 675 3777
The Netherlands* 00800 2255 4835
New Zealand 0800 800 238
Norway 800 16098
People's Republic of China 400 820 5835
Philippines 1 800 1601 0077
Poland +41 52 675 3777
Portugal 80 08 12370
Republic of Korea +82 2 6917 5000
Russia / CIS +7 (495) 6647564
Singapore 800 6011 473
South Africa +41 52 675 3777
Spain* 00800 2255 4835
Sweden* 00800 2255 4835
Switzerland* 00800 2255 4835
Taiwan 886 (2) 2656 6688
Thailand 1 800 011 931
United Kingdom / Ireland* 00800 2255 4835
USA 1 800 833 9200
Vietnam 12060128

*** European toll-free number. If not accessible, call: +41 52 675 3777**



Find more valuable resources at TEK.COM

Copyright © Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.
041618.SBG 1KW-74250-1

