

Anritsu envision : ensure

Microwave Peak USB Power Sensors

Low Cost, Compact, and Highly Accurate Peak
Power Sensors for RF and Microwave Applications

MA24406A

Peak, 50 MHz to 6 GHz

MA24418A

Peak, 50 MHz to 18 GHz

MA24440A

Peak, 50 MHz to 40 GHz

MA24408A

Peak, 50 MHz to 8 GHz

MA24419A

Peak, 50 MHz to 18 GHz

MA24441A

Peak, 50 MHz to 40 GHz



Introduction

The MA244xxA Series of Microwave Peak Power Sensors are designed to provide accurate, peak power measurements from 50 MHz to 6 GHz, 8 GHz, 18 GHz, and 40 GHz with up to 80 dB of dynamic range and 195 MHz of video bandwidth. The sensors employ a parallel processing methodology that performs the multi-step process of RF power measurement at incredible, unmatched speeds. While conventional power meters and USB sensors perform steps serially, resulting in long re-arm times and missed data, Anritsu sensors capture, display, and measure every pulse, glitch, and detail with virtually no gaps in data and zero latency.

Features and Benefits

- 6 GHz, 8 GHz, 18 GHz, and 40 GHz RF Power Sensors
- Up to 195 MHz video bandwidth with 3 ns rise time
- 100,000 measurements per second
- 10 GSa/s effective sample rate
- 100 MSa/s continuous sample rate
- Crest factor and statistical measurements (e.g. CCDF)
- Synchronized multi-channel measurements
- Microwave Peak Power Analyzer advanced measurement and analysis software



MA244xxA Microwave Peak Power Sensors

Table of Contents

Definitions 3

Performance Specifications 4

 Measurement Range 4

 VSWR 4

 Response 4

 Triggering 4

 Internal Trigger 4

 External Trigger 4

General 5

 PC Requirements 5

 Connector Type 5

 Size and Weight 5

 Warranty 5

 Environmental Requirements 5

 Regulatory Compliance 5

Ordering Information 6

 Available Models 6

 Available Options 6

 Included Accessories 6

Optional Accessories 6

 Attenuators 6

 Fixed Attenuators 6

 Coaxial Adapters 7

Definitions

Warm-Up Time	60 minutes
Operating Temperature Range	0 °C to 50 °C
Characteristic Performance	Characteristic specifications are not tested and are not warranted.
Calibration Cycle	Anritsu recommended calibration interval is 12 months.
	All specifications subject to change without notice. For the most current data sheet, please visit the Anritsu web site: www.anritsu.com

Performance Specifications

Measurement Range					
	Model	Frequency Range	Dynamic Range (Average)	Dynamic Range (Pulse)	
a. -53 dBm >6 GHz, -60 dBm < 6 GHz b. -43 dBm >6 GHz, -50 dBm < 6 GHz	MA24406A	50 MHz to 6 GHz	-60 to +20 dBm	-50 to +20 dBm	
	MA24408A	50 MHz to 8 GHz	-53 ^a to +20 dBm	-43 ^b to +20 dBm	
	MA24418A	50 MHz to 18 GHz	-34 to +20 dBm	-24 to +20 dBm	
	MA24419A	50 MHz to 18 GHz	-50 to +20 dBm	-40 to +20 dBm	
	MA24440A	50 MHz to 40 GHz	-34to +20 dBm	-24 to +20 dBm	
	MA24441A	50 MHz to 40 GHz	-50 to +20 dBm	-40 to +20 dBm	
	Input Damage Level	+23 dBm, ±10.0 VDC (+30 dBm peak for 1 μs), minimum			
VSWR					
	Model	Frequency Range	VSWR		
	MA24406A	50 MHz to 6 GHz	1.25:1		
	MA24408A	50 MHz to 6 GHz	1.20:1		
		>6.0 GHz to 8 GHz	1.25:1		
	MA24418A	50 MHz to 2 GHz	1.15:1		
		>2.0 GHz to 16 GHz	1.28:1		
		>16 GHz to 18 GHz	1.34:1		
	MA24419A	50 MHz to 2 GHz	1.15:1		
		>2.0 GHz to 6 GHz	1.20:1		
		>6.0 GHz to 16 GHz	1.28:1		
		>16 GHz to 18 GHz	1.34:1		
	MA24440A	50 MHz to 4 GHz	1.25:1		
		>4.0 GHz to 38 GHz	1.65:1		
		>38 GHz to 40 GHz	2.00:1		
	MA24441A	50 MHz to 4 GHz	1.25:1		
		>4.0 GHz to 38 GHz	1.65:1		
		>38 GHz to 40 GHz	2.00:1		
Response					
		Single Channel Rise Tiime		Video Bandwidth	
	Model	Fast	Standard	Fast	Standard
	MA24406A	3 ns	<10 μs	195 MHz	350 kHz
	MA24408A	4 ns	<10 μs	165 MHz	350 kHz
	MA24418A	5 ns	<10 μs	70 MHz	350 kHz
	MA24419A	<100 ns	<10 μs	6 MHz	350 kHz
	MA24440A	5 ns	<10 μs	70 MHz	350 kHz
	MA24441A	<100 ns	<10 μs	6 MHz	350 kHz
	Sampling Rate	100 MSa/s, characteristic			
	Effective Sampling Rate	10 GSa/s, characteristic			
Triggering					
	Source	Continuous, Internal, External TTL, Crossover (from another sensor)			
	Arm Type	Continuous, Single, Trigger Holdoff, Frame (gap) Holdoff			
	Slope	Positive or Negative			
	Trigger Hold Off	100 ns to 1 s with 10 ns resolution			
Internal Trigger					
			Minimum Pulse Width		
	Model	Dynamic Range	Fast	Standard	
	MA24406A	-38 to +20 dBm	10 ns	3 μs	
	MA24408A	-38 to +20 dBm	10 ns	3 μs	
	MA24418A	-10 to +20 dBm	10 ns	3 μs	
	MA24419A	-27 to +20 dBm	200 ns	3 μs	
	MA24440A	-10 to +20 dBm	10 ns	3 μs	
	MA24441A	-27 to +20 dBm	200 ns	3 μs	
External Trigger					
	External Trigger Input	SMB (female)			
	Impedance	10 kΩ			
	Type	TTL			
	High Level Input Voltage	2.4 V min, 5.5 V max			
	Low Level Input Voltage	-0.1 V min, 0.7 V max			
	Latency	< 10 ns (Latency is defined as the time delay between the defined edge of the applied trigger and the sensor switching into the triggered state.)			
	Trigger Pulse Width	10 ns min			
	Trigger Repetition Period	20 ns min			

General**PC Requirements**

Processor	1.3 GHz or higher recommended
RAM	512 MB (1 GB or more recommended)
Operating System	Microsoft® Windows® 7 to 10 (32-bit and 64-bit)
Hard-Disk Free Space	Min 1.0 GB free space to install and run
Display Resolution	800 x 600 (1280 x 1024 or higher recommended)
Interface	USB 2.0 high speed
Interface to Host	USB 2.0 high speed

Connector Type

RF Connector	N male to 20 GHz K male (ruggedized) to 40 GHz
--------------	---

Size and Weight

Size	145 mm x 43 mm x 43 mm, excluding N connector
Weight	363 g (0.80 lb)

Warranty

Warranty	3 year
----------	--------

Environmental Requirements Tests were performed per MIL-28800F (Class3).

Operating Temperature Range	0 °C to 55 °C
Storage Temperature Range	-40 °C to +70 °C
Relative Humidity (non-condensing)	45 % at 50 °C
	75 % at 40 °C
	95 % at 30 °C
Altitude	3048 m operational max
Shock	30 g half-sine, 11 ms duration
Vibration	Sinusoidal: 5 Hz to 55 Hz, 3 g max
	Random: 10 Hz to 500 Hz, 2.34 g rms
	Power Spectral Density: 0.01 g ² /Hz

Regulatory Compliance

European Union	EMC Directive 2014/30/EU, EN 61326:2013 CISPR 11/EN 55011:2019+A1:2010 Class A Equipment IEC/EN 61000-4-2/3/4/6 Low Voltage Directive 2014/35/EU EN 61010-1:2001 RoHS Directive 2015/863/EU
----------------	--

Ordering Information

Available Models

MA24406A	50 MHz to 6 GHz
MA24408A	50 MHz to 8 GHz
MA24418A	50 MHz to 18 GHz
MA24419A	50 MHz to 18 GHz
MA24440A	50 MHz to 40 GHz
MA24441A	50 MHz to 40 GHz

Available Options

MA24406A-097	Accredited Calibration to ISO/IEC 17025 and ANSI/NCSL Z540-1 or ANSI/NCSL Z540.3 (includes test report, uncertainty data, and accreditation symbol)
MA24408A-097	Accredited Calibration to ISO/IEC 17025 and ANSI/NCSL Z540-1 or ANSI/NCSL Z540.3 (includes test report, uncertainty data, and accreditation symbol)
MA24418A-097	Accredited Calibration to ISO/IEC 17025 and ANSI/NCSL Z540-1 or ANSI/NCSL Z540.3 (includes test report, uncertainty data, and accreditation symbol)
MA24419A-097	Accredited Calibration to ISO/IEC 17025 and ANSI/NCSL Z540-1 or ANSI/NCSL Z540.3 (includes test report, uncertainty data, and accreditation symbol)

Included Accessories

11410-00976	Information Card
806-390-R	0.9 m BNC (m) to SMB (m) cable
806-389-R	0.9 m SMB (m) to SMB (m) cable
806-391-R	1.8 m USB A (m) to USB B (m) cable

Optional Accessories

Attenuators

Accessory	Description
-----------	-------------



3-1010-122
20 dB, 5 W, DC to 12.4 GHz, N(m) to N(f)



3-1010-123
30 dB, 50 W, DC to 8.5 GHz, N(m) to N(f)



3-1010-124
Attenuator, 40 dB, 100 W, DC-8.5 GHz, N(f) input to N(m) output, Unidirectional

Accessory	Description
-----------	-------------



42N50-20
20 dB, 5 W, DC to 18 GHz, N(m) to N(f)



42N50A-30
30 dB, 50 W, DC to 18 GHz, N(m) to N(f)

Fixed Attenuators

Accessory	Description
-----------	-------------



41KB-3
Precision, DC to 26.5 GHz, 1W, 3 dB, K(m) to K(f)

41KB-6
Precision, DC to 26.5 GHz, 1W, 6 dB, K(m) to K(f)

41KB-10
Precision, DC to 26.5 GHz, 1W, 10 dB, K(m) to K(f)

41KB-20
Precision, DC to 26.5 GHz, 1W, 20 dB, K(m) to K(f)

41KC-3
Precision, DC to 40 GHz, 1W, 3 dB, K(m) to K(f)

41KC-6
Precision, DC to 40 GHz, 1W, 6 dB, K(m) to K(f)

41KC-10
Precision, DC to 40 GHz, 1W, 10 dB, K(m) to K(f)

41KC-20
Precision, DC to 40 GHz, 1W, 20 dB, K(m) to K(f)

Accessory	Description
-----------	-------------



43KC-3
Precision, DC to 26.5 GHz, 1W, 3 dB, K(m) to K(f)

43KC-6
Precision, DC to 26.5 GHz, 1W, 6 dB, K(m) to K(f)

43KC-10
Precision, DC to 26.5 GHz, 1W, 10 dB, K(m) to K(f)

43KC-20
Precision, DC to 26.5 GHz, 1W, 20 dB, K(m) to K(f)

Coaxial Adapters

Accessory	Description
	34AN50 Precision Adapter, DC to 18 GHz, GPC-7 to N(m), 50 Ω
	34ANF50 Precision Adapter, DC to 18 GHz, GPC-7 to N(f), 50 Ω
	34NK50 Precision Adapter, DC to 18 GHz, N(m) to K(m), 50 Ω
	34NKF50 Precision Adapter, DC to 18 GHz, N(m) to K(f), 50 Ω
	33NFnF50B Calibration Grade Adapter, DC to 18 GHz, N(f) to N(f), 50 Ω
	33NNF50B Calibration Grade Adapter, DC to 18 GHz, N(m) to N(f), 50 Ω
	34NN50A Calibration Grade Adapter, DC to 18 GHz, N(m) to N(m), 50 Ω
	34NFK50 Precision Adapter, DC to 18 GHz, N(f) to K(m), 50 Ω

Accessory **Description**

	1091-26-R SMA(m) to N(m), DC to 18 GHz, 50 Ω
	1091-27-R SMA(f) to N(m), DC to 18 GHz, 50 Ω
	1091-80-R SMA(m) to N(f), DC to 18 GHz, 50 Ω
	1091-81-R SMA(f) to N(f), DC to 18 GHz, 50 Ω
	510-90-R 7/16 DIN(f) to N(m), DC to 7.5 GHz, 50 Ω
	510-91-R 7/16 DIN(f) to N(f), DC to 7.5 GHz, 50 Ω
	510-92-R 7/16 DIN(m) to N(m), DC to 7.5 GHz, 50 Ω
	510-93-R 7/16 DIN(m) to N(f), DC to 7.5 GHz, 50 Ω

Training at Anritsu

Anritsu has designed courses to help you stay up to date with technologies important to your job. For available training courses, visit: www.anritsu.com/training



• United States

Anritsu Americas Sales Company
450 Century Parkway, Suite 190
Allen, TX 75013, U.S.A.
Phone: +1-800-Anritsu (1-800-267-4878)

• Canada

Anritsu Electronics Ltd.
700 Silver Seven Road, Suite 120
Kanata, Ontario K2V 1C3, Canada
Phone: +1-613-591-2003
Fax: +1-613-591-1006

• Brazil

Anritsu Eletronica Ltda.
Praça Amadeu Amaral, 27 - 1 Andar
01327-010 - Bela Vista - São Paulo - SP
Brazil
Phone: +55-11-3283-2511
Fax: +55-11-3288-6940

• Mexico

Anritsu Company, S.A. de C.V.
Blvd Miguel de Cervantes Saavedra #169 Piso 1,
Col. Granada
Mexico, Ciudad de Mexico, 11520, MEXICO
Phone: +52-55-4169-7104

• United Kingdom

Anritsu EMEA Ltd.
200 Capability Green
Luton, Bedfordshire, LU1 3LU, U.K.
Phone: +44-1582-433200
Fax: +44-1582-731303

• France

Anritsu S.A.
12 avenue du Québec, Bâtiment Iris 1- Silic 612,
91140 Villebon-sur-Yvette, France
Phone: +33-1-60-92-15-50
Fax: +33-1-64-46-10-65

• Germany

Anritsu GmbH
Nemetschek Haus, Konrad-Zuse-Platz 1
81829 München, Germany
Phone: +49-89-442308-0
Fax: +49-89-442308-55

• Italy

Anritsu S.r.l.
Via Elio Vittorini 129, 00144 Roma, Italy
Phone: +39-6-509-9711
Fax: +39-6-502-2425

List Revision Date: 20200602

• Sweden

Anritsu AB
Isafjordsgatan 32C
164 40 Kista, Sweden
Phone: +46-8-534-707-00

• Finland

Anritsu AB
Teknobulevardi 3-5
FI-01530 Vantaa, Finland
Phone: +358-20-741-8100
Fax: +358-20-741-8111

• Denmark

Anritsu A/S
c/o Regus Winghouse, Ørestads Boulevard 73, 4th
floor,
2300 Copenhagen S, Denmark
Phone: +45-7211-2200

• Russia

Anritsu EMEA Ltd.
Representation Office in Russia
Tverskaya str. 16/2, bld. 1, 7th floor
Moscow 125009, Russia
Phone: +7-495-363-1694
Fax: +7-495-935-8962

• Spain

Anritsu EMEA Ltd.
Representation Office in Spain
Paseo de la Castellana, 141.
Planta 5, Edificio Cuzco IV
28046, Madrid, Spain
Phone: +34-91-572-6761

• United Arab Emirates

Anritsu EMEA Ltd.
Dubai Liaison Office
902 Aurora Tower
P O Box: 500311 - Dubai Internet City
Dubai, United Arab Emirates
Phone: +971-4-3758479
Fax: +971-4-4249036

• India

Anritsu India Private Limited
6th Floor, Indique ETA, No.38/4
Adjacent to EMC2, Doddanekundi, Outer Ring Road
Bengaluru 560048, India
Phone: +91-80-6728-1300
Fax: +91-80-6728-1301

• Singapore

Anritsu Pte. Ltd.
11 Chang Charn Road, #04-01, Shriro House
Singapore 159640
Phone: +65-6282-2400
Fax: +65-6282-2533

• P.R. China (Shanghai)

Anritsu (China) Co., Ltd.
Room 2701-2705, Tower A
New Caohejing International Business Center
No. 391 Gui Ping Road
Shanghai 200233, P.R. China
Phone: +86-21-6237-0898
Fax: +86-21-6237-0899

• P.R. China (Hong Kong)

Anritsu Company Ltd.
Unit 1006-7, 10/F.
Greenfield Tower, Concordia Plaza
No. 1 Science Museum Road
Tsim Sha Tsui East, Kowloon
Hong Kong, P.R. China
Phone: +852-2301-4980
Fax: +852-2301-3545

• Japan

Anritsu Corporation
8-5, Tamura-cho, Atsugi-shi, Kanagawa, 243-0016
Japan
Phone: +81-46-296-6509
Fax: +81-46-225-8352

• South Korea

Anritsu Corporation, Ltd.
5FL, 235 Pangyojeok-ro
Bundang-gu, Seongnam-si
Gyeonggi-do 13494, South Korea
Phone: +82-31-696-7750
Fax: +82-31-696-7751

• Australia

Anritsu Pty. Ltd.
Unit 20, 21-35 Ricketts Road
Mount Waverley, Victoria 3149, Australia
Phone: +61-3-9558-8177
Fax: +61-3-9558-8255

• Taiwan

Anritsu Company Inc.
7F, No. 316, Sec. 1, NeiHu Rd. Taipei 114, Taiwan
Phone: +886-2-8751-1816
Fax: +886-2-8751-1817