



## MIT400/2 CAT IV Insulation Testers



- **Designed for Electrical and Industrial testing**
- **Insulation testing up to 1000 V and 200 GΩ range**
- **Stabilised insulation test voltage**
- **Single range, faster continuity testing from 0.01 Ω to 1 MΩ**
- **Adjustable insulation test voltage from 10 V to 1000 V**
- **600 V Trms AC and DC voltage measurement**
- **Test result storage and Bluetooth® downloading \***
- **Live circuit detection and protection**
- **Rechargeable options for mains and car charging \***
- **CAT IV 600 V and IP54**

### DESCRIPTION

The MIT400 mk2 series insulation and continuity testers are designed not just for Electrical and Industrial, but with an exceptionally wide range of applications from electrical installations, cable testing, motor testing, automotive, ESD, panel building, avionics, maintenance etc.

Insulation testing has been enhanced with feedback controlled test voltages to limit over-voltage to 2%, rather than the industry standard 10-20%.

A variable range has been added to allow any intermediate voltage from 10 V to 1000 V in 1 V steps, where application specific test voltages are required that do not appear in the standard ranges.\*

Continuity testing is now significantly faster, and a single auto-ranging 0.01 Ω to 1.0 MΩ function replaces the "ohms" and "kOhms" ranges. Retained are the 200 mA and 20 mA test options.

Replacing the original MIT400 instruments these units feature a redesigned case, back-stand, and 6 cell battery compartment with separate fuse access.

All instruments are over-moulded for increased protection and achieve an IP54 weatherproof rating.

### THE MIT400 RANGE:

The range consists of four instruments:

|          |                                                                             |
|----------|-----------------------------------------------------------------------------|
| MIT400/2 | 250 V, 500 V and 1000 V                                                     |
| MIT410/2 | 50 V, 100 V, 250 V, 500 V and 1000 V + PI, DAR                              |
| MIT420/2 | 50 V, 100 V, 250 V, 500 V and 1000 V + PI, DAR + VAR and result storage     |
| MIT430/2 | 50 V, 100 V, 250 V, 500 V and 1000 V + PI + DAR + VAR + Bluetooth® download |

### INSULATION RESISTANCE TESTING:

The stabilised insulation test voltage is now accurate to +2% -0%. This compares to the industry standard +20%, providing a more accurate test voltage without the risk of over-voltage damage to circuits or components. The output voltage is maintained between 0 and 2% throughout the test range.

Where a non-standard test voltage is required, a variable range allows the exact test voltage to be selected from 10 V up to 1000 V. and is subject to the same stabilised output control.\*

\* Dependent on model

## MIT400/2 CAT IV Insulation Testers

### FEATURES INCLUDE:

- **Test voltages \***
  - 50 V, 100 V, 250 V, 500 V and 1000 V.
- **Variable test voltage \***
  - Adjustable test voltage from 10 V to 1000 V.
- **2% test voltage accuracy**
  - The output test voltage is maintained within the tolerance or -0% +2%
- **PASS/FAIL indication \***
  - PASS or FAIL displayed depending on threshold voltage
- **Stabilised test voltage**
  - The voltage is feedback controlled to ensure it remains within specification throughout the full test range
- **Test voltage display**
  - The actual test voltage is displayed on the smaller digital readout, with the measurement on the larger digital display.
- **Measurement range displayed \***
  - The test range is displayed during selection
- **Analogue arc**
  - The display also features an analogue arc to replicate the response of a moving coil display.
- **PI and DAR \***
  - Polarization Index (PI) and Dielectric Absorption Ratio (DAR) functions
  - Polarization Index (PI): 10 min / 1 min ratio
  - Dielectric Absorption Ratio (DAR): 60 sec / 15 sec ratio  
60 sec / 30 sec ratio
- **Timed testing \***
  - Automatically test to a time limit
- **High test range**
  - Insulation testing up to 200 GΩ at 1000 V.
- **Silicon leads**
  - High quality flexible silicon test leads are comfortable to use and prevent measurement errors on GΩ ranges above 5 GΩ.
- **Test inhibit**
  - prevents testing if voltages in excess of 25 V, 30 V, 50 V, 75 V 100 V (set by the user) are detected when making insulation tests. (Default is 50 V.)
- **Insulation buzzer**
  - The buzzer can be set to buzz if the insulation resistance is above a user adjustable limit, set in the Setup menu.
- **Test Lock**
  - Holds insulation test on continuously.

\* Dependent on model

Test ranges extend from 2 GΩ to 200 GΩ depending on test voltage as below:\*

- 50 Volts.            10 GΩ
- 100 Volts.        20 GΩ
- 250 Volts.        50 GΩ
- 500 Volts.        100 GΩ
- 1000 Volts        200 GΩ
- Variable 10 V to 1000 V dependent on test voltage

### CONTINUITY (RESISTANCE) TESTING:

- **Single resistance range**
  - One range fully automatic from 0.01 Ω to 1.0 MΩ.
- **Bi-directional testing \***
  - Option for automatic bi-directional testing without reconnecting leads.
- **200 mA or 20 mA \***
  - Either 200 mA or 20 mA continuity test currents are available. 20 mA test current will considerably increase battery life.
- **Lead null**
  - Lead resistance compensation (NULL) operates up to 10 Ω of resistance.
- **Buzzer**
  - ON/OFF selected by simple push button.
- **Buzzer limit**
  - Continuity buzzer limit alarm provides adjustment of the maximum resistance the continuity buzzer sounds. This is adjustable from 1 Ω to 200 Ω in 12 steps.

### VOLTAGE MEASUREMENT:

True RMS voltage measurement to 600 V ac or dc with resolution from 0.1 mV.

- Digital voltage measurement up to 600 V ac/dc
- Analogue arc measurement to 600 V ac/dc
- Automatic display of frequency during voltage measurement.

### DISPLAY:

The display offers a combination of Analogue arc and a dual digital readout:

Analogue arc:

- Full display width analogue arc.
- Analogue arc display shows essential charge and discharge characteristics not visible on a digital display.
- Single pointer "needle" response is similar to a moving coil meter.
- Setup functions allow control of Buzzer limit alarms, Continuity test currents

### DUAL DIGITAL DISPLAY

- Large main digital readout for good visibility of all main measurement results
- Second digital display for additional data such as:
  - Insulation test voltage.
  - Insulation leakage current.
  - Supply frequency (when measuring volts).
  - Test mode eg. PI, DAR or t ( t = Timer mode).

## MIT400/2 CAT IV Insulation Testers

### OTHER FUNCTIONS AND FEATURES

**Weatherproof** - Every tester is sealed to IP54, providing a weatherproof case to reduce the chances of water ingress, including the battery and fuse compartment.

**Tough housing** - Rubber over moulding combines the tough shock absorbing outer protection with excellent grip, on a strong modified ABS housing, providing an almost indestructible case.

**Batteries** - Battery requirements are 6 AA batteries of either standard Alkaline or Nickel Metal Hydride (NiMH) rechargeable type, providing a minimum of 3000 insulation tests at 1000 V.

### VARIABLE INSULATION VOLTAGE TESTER \*

The variable mode provides a solution for unique insulation voltage measurement applications. The range option allows any insulation test voltage to be set between 10 V and 1000 V in 1 V steps.

\* Dependent on model

### TYPICAL APPLICATIONS INCLUDE:

- Commercial Avionics
- Military Land, Marine and Air communications
- Manufacturing/production line goods
- Electrostatic measurement
- Component testing
- Battery powered traction and lifting equipment

### STORAGE AND DOWNLOADING RESULTS \*

Smooth Bluetooth<sup>®</sup> and pairing procedures make the MIT430/2 easy to pair and download data. The test results are downloaded to a CSV file which can then be opened as an Excel<sup>®</sup> spreadsheet.

### SAFETY

Designed to be exceptionally safe to use, fast detecting circuitry prevents damage to the instruments if accidentally connected to live circuits or across phases. Specifically, all instruments:

Meet the international requirements of IEC61010 and EN61557.

Live circuit detection inhibits insulation testing on circuits above 25 V, 30 V, 50 V, 75 V or 100 V (default 50 V).

Live circuit detection and test inhibit on continuity measurements.

Default display of live circuit voltage on all ranges.

Detection and inhibit functions even if the protection fuse has failed.

Suitable for use on CAT IV applications and supply voltages to 600 V.

### FEATURES AND BENEFITS

- Designed for Electrical and Industrial testing
- Insulation testing up to 1000 V and 200 GΩ range
- Stabilised insulation test voltage
- Single range, faster continuity testing from 0.01 Ω to 1 MΩ
- Adjustable insulation test voltage from 10 V to 1000 V \*
- 600 V Trms AC and DC voltage measurement
- Updated case design with optional magnetic hanging strap
- Test result storage and Bluetooth<sup>®</sup> downloading \*
- Live circuit detection and protection
- Rechargeable options for mains and car charging \*
- CAT IV 600 V and IP54

## MIT400/2

### CAT IV Insulation Testers

#### SPECIFICATION SUMMARY TABLE

| INSULATION                           | MIT400/2 | MIT410/2 | MIT420/2 | MIT430/2 |
|--------------------------------------|----------|----------|----------|----------|
| 50 V / 100 V                         |          | ■        | ■        | ■        |
| 250 V / 500 V / 1000 V               | ■        | ■        | ■        | ■        |
| Variable                             |          |          | ■        | ■        |
| PI- / DAR / Timed                    |          | ■        | ■        | ■        |
| Lock button on MΩ                    | ■        | ■        | ■        | ■        |
| Leakage current display              |          | ■        | ■        | ■        |
| <b>CONTINUITY</b>                    |          |          |          |          |
| Continuity 0.01 Ω - 1 MΩ             | ■        | ■        | ■        | ■        |
| Auto reverse polarity (setup ON-OFF) |          | ■        | ■        | ■        |
| Lead null (< 10 Ω)                   | ■        | ■        | ■        | ■        |
| <b>VOLTAGE</b>                       |          |          |          |          |
| AC / DC Volts 600 V                  | ■        | ■        | ■        | ■        |
| mV AC / DC range                     | ■        | ■        | ■        | ■        |
| Frequency measurement 15 - 400 Hz    |          | ■        | ■        | ■        |
| Input impedance 0.25 MΩ              | ■        | ■        | ■        | ■        |
| <b>CAPACITANCE</b>                   |          |          |          |          |
| Capacitance 0.1 nF - 10 μF           |          |          | ■        | ■        |
| <b>OTHER FEATURES</b>                |          |          |          |          |
| PASS/FAIL on limit alarms            |          | ■        | ■        | ■        |
| Auto power down (setup)              | ■        | ■        | ■        | ■        |
| On board memory                      |          |          | ■        | ■        |
| Bluetooth® download + software       |          |          |          | ■        |
| Can use AA Alkaline or NiMH          | ■        | ■        | ■        | ■        |
| On-board charging (optional charger) |          |          |          | ■        |
| CAT IV 600 V / CAT III 1000 V        | ■        | ■        | ■        | ■        |
| <b>ACCESSORIES</b>                   |          |          |          |          |
| Silicone leads (red/black)           | ■        | ■        | ■        | ■        |
| Switched probe supplied              |          | ■        | ■        | ■        |
| OPTIONAL Battery charger available   |          |          |          | ■        |

## MIT400/2 CAT IV Insulation Testers

### SPECIFICATION

All quoted accuracies are at +20 °C.

#### Insulation:

##### Test voltage

|                        |                                   |
|------------------------|-----------------------------------|
| Nominal:               |                                   |
| MIT400/2               | 250 V, 500 V, 1000 V              |
| MIT410/2, 420/2, 430/2 | 50 V, 100 V, 250 V, 500 V, 1000 V |

##### Insulation accuracy

|            |        |                               |
|------------|--------|-------------------------------|
| 50 Volts.  | 10 GΩ  | ± 2% ± 2 digits ± 4.0% per GΩ |
| 100 Volts. | 20 GΩ  | ± 2% ± 2 digits ± 2.0% per GΩ |
| 250 Volts. | 50 GΩ  | ± 2% ± 2 digits ± 0.8% per GΩ |
| 500 Volts. | 100 GΩ | ± 2% ± 2 digits ± 0.4% per GΩ |
| 1000 Volts | 200 GΩ | ± 2% ± 2 digits ± 0.2% per GΩ |

Service Error: BS EN 61557-2 (2007).

|        |                                      |
|--------|--------------------------------------|
| 50V,   | ± 2.0% ± 2d, 100 kΩ - 900 kΩ ± 10.5% |
| 100V,  | ± 2.0% ± 2d, 100 kΩ - 900 kΩ ± 10.3% |
| 250V,  | ± 2.0% ± 2d, 100 kΩ - 900 kΩ ± 10.3% |
| 500V,  | ± 2.0% ± 2d, 100 kΩ - 900 kΩ ± 10.3% |
| 1000V, | ± 2.0% ± 2d, 100 kΩ - 900 kΩ ± 11.5% |

|                                        |                                                                                  |
|----------------------------------------|----------------------------------------------------------------------------------|
| <b>Display range</b>                   | Analogue:<br>1 GΩ full scale                                                     |
| <b>Resolution</b>                      | 0.1 kΩ                                                                           |
| <b>Short circuit/charge current</b>    | 2 mA +0% -50% to EN 61557-2 (2007)                                               |
| <b>Open circuit voltage insulation</b> | -0% +2% ± 2V                                                                     |
| <b>Test current</b>                    | 1 mA at min. pass value of insulation to a maximum of 2 mA max.                  |
| <b>Leakage</b> (not MIT400/2)          | 10% ± 3 digits                                                                   |
| <b>Voltage</b>                         | 3% ± 3 digits ± 0.5% of rated voltage                                            |
| <b>Timer control</b> (not MIT400/2)    | 60 second countdown timer                                                        |
| <b>Note</b>                            | Above specifications only apply when high quality silicone leads are being used. |

#### Continuity:

|                                |                                                                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Continuity measurement</b>  | 0.01 Ω to 1000 kΩ                                                                                                                                                |
| <b>Continuity accuracy</b>     | ± 3% ± 2 digits (0 to 100 Ω)<br>± 5% ± 2 digits (100 to 500kΩ)<br>(500kΩ to 1MΩ unspecified)<br>Service Error: BS EN 61557-4 (2007) - ± 2.0%, 0.1 Ω - 2 Ω ± 6.8% |
| <b>Open circuit voltage</b>    | 5 V ± 1 V                                                                                                                                                        |
| <b>Test current</b>            | 200 mA (-0 mA +20 mA)<br>(0.01 Ω to 4 Ω)                                                                                                                         |
| <b>Polarity</b> (not MIT400/2) | Single polarity (Default) /<br>Dual polarity (configurable on setup).                                                                                            |

|                                                |                                                                                                                                                                                                                               |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Lead resistance</b>                         | Null up to 9.00 Ω                                                                                                                                                                                                             |
| <b>Voltage:</b>                                |                                                                                                                                                                                                                               |
| <b>Voltage range</b>                           | AC: 10 mV to 600 V TRMS sinusoidal (15 Hz to 400 Hz)<br>DC: 0 to 600 V                                                                                                                                                        |
| <b>Volt range accuracy</b>                     | AC: ± 2% ± 1 digit<br>DC: ± 2% ± 2 digit<br>Service Error: BS EN 61557-1 (2007) - ± 2.0% ± 2d, 0 V - 300 V AC/DC ± 5.1%                                                                                                       |
| <b>Waveform</b>                                | Unspecified range:<br>0 - 10 mV (15 to 400 Hz)<br>For non-sinusoidal waveforms additional specifications apply<br>Non-sinusoidal waveforms:<br>± 3% ± 2 digits > 100 mV to 600 V TRMS<br>± 8% ± 2 digits 10 mV to 100 mV TRMS |
| <b>Frequency:</b> (not MIT400/2)               |                                                                                                                                                                                                                               |
| <b>Frequency measurement range</b>             | 15 Hz - 400 Hz                                                                                                                                                                                                                |
| <b>Frequency measurement accuracy</b>          | ± 0.5% ± 1 digit (100 Hz to 400 Hz unspecified)                                                                                                                                                                               |
| <b>Capacitance measurement:</b>                | MIT420/2, MIT430/2                                                                                                                                                                                                            |
| MIT420/2, MIT430/2                             |                                                                                                                                                                                                                               |
| <b>Capacitance measurement</b>                 | 1 nF to 10 μF                                                                                                                                                                                                                 |
| <b>Capacitance measurement accuracy</b>        | ± 5.0% ± 2 digits<br>(0.1 nF - 1 nF unspecified)                                                                                                                                                                              |
| <b>Storage:</b>                                |                                                                                                                                                                                                                               |
| <b>Result storage</b> (MIT420/2 and MIT430/2): |                                                                                                                                                                                                                               |
| <b>Storage capacity</b>                        | > 1000 test results                                                                                                                                                                                                           |
| <b>Data download</b> (MIT430/2 only)           | Bluetooth® wireless<br>Bluetooth® Class II                                                                                                                                                                                    |
| <b>Range</b>                                   | up to 10 m                                                                                                                                                                                                                    |
| <b>Power supply</b>                            | 6 x 1.5 V cells<br>type IEC LR6 (AA, MN1500, HP7, AM3 R6HP) Alkaline<br>6 x 1.2 V NiMH rechargeable cells may be used                                                                                                         |
| <b>Battery life</b>                            | 3000 insulation tests with duty cycle of 5 sec ON / 55 sec OFF @ 1000 V into 1 MΩ                                                                                                                                             |
| <b>Charger (Optional):</b>                     | 12-15 V dc (accessory interface)                                                                                                                                                                                              |
| <b>Dimensions</b>                              | Instrument 228 mm x 108 mm x 63 mm (9.00 in x 4.25 in x 2.32 in)                                                                                                                                                              |
| <b>Weight</b>                                  | 600 g (MIT400/2), (1.32 lb)                                                                                                                                                                                                   |

# MIT400/2

## CAT IV Insulation Testers

|                                     |                                                                                                                                                 |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Weight (instrument and case)</b> | 1.75 kg (3.86 lb)                                                                                                                               |
| <b>Fuse</b>                         | Use only 1 x 500 mA (FF)<br>1000 V 32 x 6 mm ceramic<br>fuse of high breaking capacity<br>HBC 30 kA minimum. Glass<br>fuses MUST NOT be fitted. |
| <b>Safety protection</b>            | The instruments meet<br>EN 61010-1 (1995) to 600<br>V phase to earth, Category<br>IV. Refer to safety warnings<br>supplied.                     |
| <b>EMC</b>                          | In accordance with IEC 61326<br>including amendment No.1                                                                                        |
| <b>Temperature co-efficient</b>     | <0,1% per °C up to 1 GΩ<br><0,1% per °C per GΩ above<br>1 GΩ                                                                                    |

### Environmental:

|                                                 |                                       |
|-------------------------------------------------|---------------------------------------|
| <b>Operating temperature range and humidity</b> | -10 to +55 °C<br>90% RH at 40 °C max. |
| <b>Storage temperature range</b>                | -25 to +70 °C                         |
| <b>Calibration temperature</b>                  | +20 °C                                |
| <b>Maximum altitude</b>                         | 2000 m                                |
| <b>IP rating</b>                                | IP 54                                 |

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc and is used under licence.

### ORDERING INFORMATION

| Description                                                        | Order Code | Description                                      | Order Code |
|--------------------------------------------------------------------|------------|--------------------------------------------------|------------|
| MIT400/2 - 250V, 500V 1000V Insulation tester                      | 1004-731   | <b>Optional Accessories</b>                      |            |
| MIT410/2 - as MIT400/2 + 50 V and 100 V, PI, DAR and timed testing | 1004-735   | UKAS calibration certificate                     | 1000-085   |
| MIT420/2 - as MIT410/2 + variable voltage test, storage and recall | 1004-739   | Mains Charger kit (MIT430/2 only)                | 1007-464   |
| MIT430/2 - as MIT420/2 + Bluetooth® and recharge ready             | 1004-740   | 12 V DC car charger (requires mains charger kit) | 1004-183   |
|                                                                    |            | SP5 remote switch probe                          | 1007-157   |
|                                                                    |            | Test lead set and crocodile clips                | 1002-001   |
|                                                                    |            | 2 wire 500 mA fused test lead set                | 1002-015   |
|                                                                    |            | Batteries (6 x NiMH)                             | 1002-735   |
|                                                                    |            | Magnetic Hanging Strap                           | 1010-013   |
|                                                                    |            | Carry Pouch MIT400/2 Series                      | 1007-887   |
| <b>Included Accessories</b>                                        |            |                                                  |            |
| Red/Black Silicone test leads with Probes + Clips                  |            |                                                  |            |
| SP5 remote switch probe (not MIT400/2)                             |            |                                                  |            |
| Batteries 6 x AA Alkaline                                          |            |                                                  |            |
| Hard carry case                                                    |            |                                                  |            |
| Calibration certificate                                            |            |                                                  |            |



**CalPlus GmbH**  
Zentrale Berlin  
Heerstraße 32 • 14052 Berlin  
Tel.: 030 214982-0 • Fax: 030 214982-50  
office@calplus.de • www.calplus.de

**CalPlus GmbH**  
Niederlassung Hamburg  
Normannenweg 30 • 20537 Hamburg  
Tel.: 040 3039595-0 • Fax: 040 3039595-50  
scopeshop@calplus.de • www.calplus.de



MIT4002\_DS\_en\_V08

www.megger.com

ISO 9001

The word 'Megger' is a registered trademark