

Passive 10X Voltage Probe

TPP0200, TPP0201 Datasheet



The TPP0200 and TPP0201 probes are 200 MHz, 10X passive voltage probes with 10 M Ω input resistance.

Key features

- 10X Attenuation
- 200 MHz Bandwidth
- 1.3 m Length
- UL61010-031; 2007, CAN/CSA C22.2 No. 61010-031-07, IEC61010-031; IEC 61010-031/A1:2008
- Applications:
 - Relative low-frequency measurements
 - Low-frequency computer and telecom measurements
 - Power supplies
 - Low-frequency amplifiers

TPP0200, TPP0201 Passive Voltage probes

The TPP0200 and TPP0201 probes are for use on BNC oscilloscopes with 1 M Ω /13 pF (TPP0200) and 1 M Ω /20 pF (TPP0201) inputs.

For a complete list of compatible oscilloscopes, refer to the Tektronix Oscilloscope Probe & Accessory Selector Tool at <http://www.tek.com/probes>.

Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

Electrical characteristics

Bandwidth	DC to 200 MHz
Rise time	<2.3 ns (typical)
Compensation range	
TPP0200	8 pF to 18 pF
TPP0201	15 pF to 25 pF
Input resistance	10 M Ω $\pm$ 1.5%
Input capacitance	<12 pF (typical)
Propagation delay	~6.1 ns
Maximum input voltage	300 V _{RMS} CAT II

Physical characteristics

Probe cable length	1.3 m (4.2 ft)
--------------------	----------------

EMC, environment, and safety

Temperature range	
Operating	-10 °C to +55 °C (14 °F to 131 °F)
Non-operating	-51 °C to +71 °C (-60 °F to 160 °F)
Humidity	
Operating and non-operating	5% to 95% relative humidity (%RH) up to 30 °C (86 °F), 5% to 65% RH above +30 °C (86 °F) up to +55 °C (131 °F)
Altitude	
Operating	<3 km (9,842 ft)
Non-operating	<12.2 km (40,026 ft)

Ordering information

TPP0200	For use with BNC oscilloscopes with 1 M Ω , 13 pF inputs
TPP0201	For use with BNC oscilloscopes with 1 M Ω , 20 pF inputs

Probe packages

TPP0201-PK10	10-pack of TPP0201 probes
TPP0201-PK50	50-pack of TPP0201 probes

Standard accessories

003-1433-xx	Adjustment tool
013-0362-xx	Retractable hook tip
016-0633-xx	Color bands, 5 pairs
016-2028-xx	Long ground spring, 2 each
196-3521-xx	6 in. alligator ground lead

Warranty

One-year warranty covering all parts and labor.

Recommended accessories

196-3556-xx	Electrical Y-lead
013-0363-xx	Micro hook tip
013-0366-xx	Universal IC cap
013-0367-xx	BNC-to-probe tip adapter, unterminated
016-2016-xx	PCB-to-probe tip adapter, 10-pack
016-2034-xx	Short ground spring, 2 each
131-8831-xx	Compact probe-tip chassis mount
196-3198-xx	6 in. clip-on ground lead with 0.025 in. pin receptacle
196-3512-xx	12 in. alligator ground
206-0569-xx	MicroCKT test tip



Tektronix is ISO 14001:2015 and ISO 9001:2015 certified by DEKRA.



CalPlus GmbH
Zentrale Berlin
Heerstraße 32 • 14052 Berlin
Tel.: 030 214982-0 • Fax: 030 214982-50
office@calplus.de • www.calplus.de

CalPlus GmbH
Niederlassung ScopeShop
Normannenweg 30 • 20537 Hamburg
Tel.: 040 3039595-0 • Fax: 040 3039595-50
scopeshop@calplus.de • www.calplus.de

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

17 Sep 2024 51W-25681-5
tek.com

Tektronix®