

Probe Power Supply

1103 Datasheet



1103 TekProbe Power Supply.

Features & Benefits

1103

- Powers up to Two Probes
- For Use with P6205, P6243, P6245, P6246, P6247, P6248, P6249, P6330, P6701B, P6703B, P5205, P5210, ADA400A, and TCP202 on other than TekProbe BNC Interfaced Scopes*1
- Overload Protected 1103

Applications

- High-speed Digital Systems Design
 - ECL
 - GaAs
 - MOS: CMOS; FastCMOS; BiCMOS; TTL
- Component Design/Characterization
 - Amplitude levels
 - Aberrations
 - Propagation Delay and Timing
 - Bandwidths and Rise Times
- Educational Research
- Manufacturing Engineering and Test

TekProbe BNC™ Interface

The 1103 is an accessory power supply that provides external power to TekProbe BNC Interface probes. The 1103 allows customers to use probes requiring TekProbe interface power with any oscilloscope or digitizer that does not provide TekProbe BNC power.

The 1103 offers two independently controlled channels consisting of a TekProbe BNC interface input, a voltage offset control (providing variable offset or no offset) and BNC signal output.

The offset control supplies a voltage, adjustable via the front panel control. This offset control is available for TekProbe BNC probes with this capability. These include: P6235, P6245, P6246, P6247, P6248, P6249, and P6330.

*1 The characteristics for TekProbe BNC Interface probes are subject to change when used with the 1103 TekProbe Power Supply. Bandwidth, Rise-time, Propagation Delays will generally differ from the advertised probe only specification. These are dependent upon: 1) the cable length from the output BNC connector to the oscilloscope input, 2) the instrumentation input impedance the output BNC is being connected to, and 3) any additional adapters required to properly interface to the test instrumentation.

To use TekProbe BNC Interface probes on the 11800, CSA800, TDS8000, CSA8000 or any non-TekProbe BNC interface test instrumentation requires an 1103 TekProbe Power Supply, an SMA Male to BNC Female adapter, a 50 Ω BNC cable and if required a 50 Ω feedthrough termination.

Characteristics

Output Voltage $\pm 2\%$ – +15 V, -15 V, +5 V, -5 V.

Output Current – 300 mA.

Outputs – Pin 1: n.c.

Pin 2: n.c.

Pin 3: +5 V.

Pin 4: +15 V.

Pin 5: Offset ± 1 V.

Pin 6: -5 V.

Pin 7: -15 V.

Power Consumption – ≤ 35 W.

Physical Characteristics

Dimension	cm	in.
Depth	17.8	7
Width	15.8	6.2
Height	8.9	3.9
Weight	kg	lb.
Net	1.8	3.9

ASEAN / Australasia (65) 6356 3900

Austria 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777

Belgium 00800 2255 4835*

Brazil +55 (11) 3759 7627

Canada 1 800 833 9200

Central East Europe and the Baltics +41 52 675 3777

Central Europe & Greece +41 52 675 3777

Denmark +45 80 88 1401

Finland +41 52 675 3777

France 00800 2255 4835*

Germany 00800 2255 4835*

Hong Kong 400 820 5835

India 000 800 650 1835

Italy 00800 2255 4835*

Japan 81 (3) 6714 3010

Luxembourg +41 52 675 3777

Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90

Middle East, Asia, and North Africa +41 52 675 3777

The Netherlands 00800 2255 4835*

Norway 800 16098

People's Republic of China 400 820 5835

Poland +41 52 675 3777

Portugal 80 08 12370

Republic of Korea 001 800 8255 2835

Russia & CIS +7 (495) 7484900

South Africa +41 52 675 3777

Spain 00800 2255 4835*

Sweden 00800 2255 4835*

Switzerland 00800 2255 4835*

Taiwan 886 (2) 2722 9622

United Kingdom & Ireland 00800 2255 4835*

USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

Ordering Information

1103

TekProbe® Power Supply.

For P6205, P6235, P6243, P6245, P6246, P6247, P6248, P6249, P6330, P6701B, P6703B, P5205, P5210, ADA400A, and TCP202. Powers two probes.

Please specify power plug when ordering.

Power Plug Options

Opt. A0 – US Plug, 115 V, 60 Hz.

Opt. A1 – Euro Plug, 220 V, 50 Hz.

Opt. A2 – UK Plug, 240 V, 50 Hz.

Opt. A3 – Australian Plug, 240 V, 50 Hz.

Opt. A4 – N. American Plug, 240 V, 50 Hz.

Opt. A5 – Swiss Plug, 220 V, 50 Hz.

Service

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Opt. SILV600 – Standard Warranty Extended to 5 Years.

Additional Accessories

36 in. Precision 50 Ω BNC Cable – Order 012-0482-00.

50 Ω Feedthrough Termination – Order 011-0049-02.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

