

# Active Probes

## TAP2500 - TAP3500 - TAP4000 Datasheet



The TAP2500, TAP3500 and TAP4000 Single-ended Active FET probes provide excellent high-speed electrical and mechanical performance required for today's digital system designs.

### Key features

- Outstanding electrical performance
  - High probe bandwidth
  - Fast probe rise time
  - Excellent signal fidelity
  - $\leq 0.8$  pF input capacitance
  - 40 k $\Omega$  input resistance
  - -4 V to +4 V input dynamic range
  - -10 V to +10 V<sub>DC</sub> input offset range
  - $\pm 30$  V (DC + peak AC) Maximum input voltage (nondestructive)
- Versatile mechanical performance
  - Small compact probe head for probing small geometry circuit elements
  - DUT attachment accessories enable connection to SMDs as small as 0.5 mm pitch
  - Robust design for reliability

- Easy to use
  - Connects directly to oscilloscopes with the TekVPI™ probe interface
  - Provides automatic units scaling and readout on the oscilloscope display
  - Easy access to oscilloscope probe menu display for probe status/ diagnostic information and to control probe DC offset
  - Remote GPIB/USB probe control through the oscilloscope
- Applications
  - Verification, debug, and characterization of high-speed designs
  - Signal integrity, jitter, and timing analysis
  - Manufacturing engineering and test
  - Signals with voltage swings up to 8 V<sub>p-p</sub>



## TAP2500, TAP3500 and TAP4000 active probes for TekVPI™ probe interface

Selecting the right probe for your application is key to attaining the best signal fidelity in your measurements. Active probes provide truer signal reproduction and fidelity for high-frequency measurements. With our ultra-low input capacitance and unique interface, the TAP2500, TAP3500 and TAP4000 Single-ended Active FET probes provide excellent high-speed electrical and mechanical performance required for today's digital system designs.

Specifically designed for use and direct connection to oscilloscopes with the TekVPI™ probe interface, the TAP2500, TAP3500 and TAP4000 Active FET probes achieve high-speed signal acquisition and measurement fidelity by solving three traditional problems:

- Lower DUT loading effects with  $\leq 0.8$  pF input capacitance and 40 k $\Omega$  input resistance
- Versatile DUT connectivity for attaching to small SMDs
- Preserves instrument bandwidth at the probe tip for up to 3.5 GHz oscilloscopes

## Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

### Warranted electrical characteristics

Attenuation (probe only)	10X
Rise time (probe only)	<140 ps (TAP2500) <130 ps (TAP3500)

### Typical characteristics

Bandwidth (probe only)	$\geq 2.5$ GHz (TAP2500) $\geq 3.5$ GHz (TAP3500) $\geq 4$ GHz (TAP4000)
Rise time (probe only)	$\leq 115$ ps (TAP4000)
Input capacitance	$\leq 0.8$ pF
Input resistance	40 k $\Omega$
Input dynamic range	$\pm 4.0$ V
Input offset range	$\pm 10$ V
Maximum non-destructive input voltage	$\pm 30$ V (DC + peak AC)
Propagation delay	5.3 ns

## Physical characteristics

### Probe head size

Height	7.6 mm (0.30 in)
Width	7.6 mm (0.30 in)
Length	57.2 mm (2.25 in)

### Other dimensions

Cable length	1300 mm (51 in)
--------------	-----------------

### Weight

Unit	1.55 kg (3.44 lbs) (probes, accessories, and packaging)
Net	0.091 kg (0.2 lbs) (probe only, using ME lab scale)

## Power requirements

The probe is powered directly by oscilloscopes with the TekVPI probe interface.

## EMC, environment, and safety

### Temperature

Operating	0 °C to +50 ° (+32 °F to 122 °F)
Nonoperating	-40 °C to +71 °C (-40 °F to 160 °F)

### Humidity

Operating	5% to 95% Relative Humidity up to +30 °C (+86 °F) 5% to 85% Relative Humidity at 30 °C to +50 °C (+86 °F to +122 °F) noncondensing
Nonoperating	5% to 95% Relative Humidity up to +30 °C (+86 °F) 5% to 85% Relative Humidity at 30 °C to +75 °C (+86 °F to +167 °F) noncondensing

### Altitude

Operating	Up to 4,400 m (14,436 ft)
Nonoperating	Up to 12,192 m (40,000 ft)

Emissions compliance EN 55011, Class A

### Regulatory

Compliance labeling	C-Tick (Australia/New Zealand)
	CE (European Union)
	WEEE (European Union)

## Ordering information

### Models

TAP2500	2.5 GHz Active Probe
TAP3500	3.5 GHz Active Probe
TAP4000	4 GHz Active Probe

## Standard accessories

### Standard accessories

Description	Quantity with TAP2500, TAP3500 or TAP4000	Reorder part number	Reorder quantity
Y-lead adapter (2 each) and 3 in. ground lead (3 each)	1 set	196-3456-xx	1 set
Micro CKT test tip	2 each	206-0569-xx	1 each
Customizable ground lead (set of 5)	1 set	196-3482-xx	1 set
Color band kit (5 colored pairs)	1 set	016-1315-xx	1 set
Pogo pin ground (set of 10)	1 set	016-1772-10	1 set
Square pin socket (set of 10)	1 set	016-1773-10	1 set
Push-in probe tip (set of 10)	1 set	131-5638-11	1 set
Right-angle adapter (set of 10)	1 set	016-1774-xx	1 set
SureToe™ Adapter (set of 4)	1 set	131-6254-xx	1 set
Antistatic wrist strap	1 each	006-3415-xx	1 each
Nylon carrying case	1 each	016-1952-xx	1 each
Plastic accessory case	1 each	006-7164-xx	1 each
Instruction manual	1 each	071-1836-xx	1 each

### Recommended oscilloscopes

Oscilloscopes with the TekVPI™ probe interface.

### Warranty

One-year warranty covering all parts and labor.

## Options

### Manual options

Opt. L5	Japanese manual
Opt. L7	Simplified Chinese manual

### Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. D1	Calibration Data Report
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R5	Repair Service 5 Years (including warranty)
Opt. SILV600	Standard warranty extended to 5 years

## Recommended accessories

013-0309-xx	IC Micro Grabber, Qty 2
015-0678-xx	SMA-to-Probe tip adapter
067-1701-xx	TekVPI calibration fixture (for PV)

CE Marking Not Applicable.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

**ASEAN / Australasia** (65) 6356 3900  
**Belgium** 00800 2255 4835\*  
**Central East Europe and the Baltics** +41 52 675 3777  
**Finland** +41 52 675 3777  
**Hong Kong** 400 820 5835  
**Japan** 81 (3) 6714 3086  
**Middle East, Asia, and North Africa** +41 52 675 3777  
**People's Republic of China** 400 820 5835  
**Republic of Korea** +822 6917 5084, 822 6917 5080  
**Spain** 00800 2255 4835\*  
**Taiwan** 886 (2) 2656 6688

**Austria** 00800 2255 4835\*  
**Brazil** +55 (11) 3759 7627  
**Central Europe & Greece** +41 52 675 3777  
**France** 00800 2255 4835\*  
**India** 000 800 650 1835  
**Luxembourg** +41 52 675 3777  
**The Netherlands** 00800 2255 4835\*  
**Poland** +41 52 675 3777  
**Russia & CIS** +7 (495) 6647564  
**Sweden** 00800 2255 4835\*  
**United Kingdom & Ireland** 00800 2255 4835\*

**Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777  
**Canada** 1 800 833 9200  
**Denmark** +45 80 88 1401  
**Germany** 00800 2255 4835\*  
**Italy** 00800 2255 4835\*  
**Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90  
**Norway** 800 16098  
**Portugal** 80 08 12370  
**South Africa** +41 52 675 3777  
**Switzerland** 00800 2255 4835\*  
**USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tek.com](http://www.tek.com).

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



16 Jul 2018 51W-19044-10

[www.tek.com](http://www.tek.com)

**Tektronix**<sup>®</sup>

**CalPlus GmbH**  
Zentrale Berlin  
Heerstraße 32 • 14052 Berlin  
Tel.: 030 214982-0 • Fax: 030 214982-50  
office@calplus.de • www.calplus.de

**CalPlus GmbH**  
Niederlassung ScopeShop  
Normannenweg 30 • 20537 Hamburg  
Tel.: 040 3039595-0 • Fax: 040 3039595-50  
scopeshop@calplus.de • www.calplus.de